



Quality Built For Life!



Daily

IVECO

ENGINE SPECIFICATION

IVECO 50-C-15 EURO 4

GVW	5000kg
Fuel	Diesel
Capacity (litres)	3.0
Cylinders	4 (16 valve)
Emission Compliance	Euro 4
Fuel System	Turbo charged & intercooled
Power (hp/kW)	146/107
@rpm	3000-3500
Torque (Nm/lbft)	350/258
@rpm	1400-2600
Alternator	14v – 140A
Battery	12v – 110Ah

IVECO 65-C-18 EURO 4

GVW	6500kg
Fuel	Diesel
Capacity (litres)	3.0
Cylinders	4 (16 valve)
Emission Compliance	Euro 4
Fuel System	Turbo charged & intercooled
Power (hp/kW)	176/130
@rpm	3200-3500
Torque (Nm/lbft)	400/295
@rpm	1250-3000
Alternator	14v – 140A
Battery	12v – 110Ah

DIMENSIONS

	50-C-15 (3.75m)	50-C-15 (3.75m Narrow Body)	50-C-15 / 65-C-18 (4.35m)	50-C-15 / 65-C-18 (4.35m Narrow body)	65-C-18 (4.75m)
Overall Length	6998mm	6998mm	7698mm	7698mm	8508mm
Overall width	2340mm	2210mm	2350mm	2210mm	2350mm
Interior Height	1830mm	1830mm	1830mm	1830mm	1830mm
Interior Width	2200mm	2060mm	2200mm	2060mm	2200mm
Saloon Length	3620mm	3620mm	4300mm	4300mm	5110mm

VEHICLE SPECIFICATION



- ◆ Aerodynamically styled front.
- ◆ Nearside door positioned behind cab area in line with Iveco build requirements.
- ◆ Moulded skirt panels continue Iveco styling.
- ◆ Radiused rear panels incorporate standard Iveco rear lamps and feature high-level rear lamps recessed into the bodywork.
- ◆ Double rear doors for wheelchair access via a lift.
- ◆ Heated front quarter light glasses/windows.
- ◆ Stepped saloon floor arrangement.
- ◆ 2 step entry on the 50-C-15 risers of 250mm, 200mm & 200mm. On the 65-C-18 risers of 325mm, 200mm & 200mm. A fold out step concealed within the first step tread reduces the step height.
- ◆ Ergonomically designed handrail layout incorporates ascending rails at stepwell, drivers protection rail with luggage pen in the nearside cab area.
- ◆ Interior is lined with purpose made moulded panels to cab, saloon roof coves and rear bulkhead.
- ◆ Main roof and lower sides are soft trimmed as standard with alternative finishes available.
- ◆ Floor area overlaid in slip resistant vinyl with high visibility mouldings at step edges.
- ◆ Saloon side windows are gasket glazed and may incorporate top opening units if required, bonded windows are available as an option.
- ◆ Heating in the saloon is an independent combustion unit to comply with Iveco build.
- ◆ Saloon seats are mounted on "Mellordec" tracking using Unwin detachable seat mechanisms. All seats are equipped with 'All Ages' inertia reel lap and diagonal seat belts.
- ◆ The seat belts, seats and fixings have been tested to the requirement of EEC 76/115 for category M2 vehicles.
- ◆ Surface mounted low profile interior lights fitted into roof cove sections. Stepwell and loading lights are also fitted.
- ◆ Miscellaneous items include a first aid kit and two fire extinguishers.
- ◆ Exterior finished in two-pack acrylic in a single non-metallic colour of your choice.

